

Lab Refrigerator, 1 Door, Upright - KG100

General Purpose Solid Door Stainless Steel Refrigerator with digital display microprocessor temperature controller. This unit features hydrocarbon natural refrigerants and sensor error alarm and remote alarm contacts.. Audible and visual high/low alarms and forced draft circulation are some of the features of this well rounded unit.



SPECIFICATIONS

Construction

- Stainless steel
- 4 swivel casters (5 3/4")
- Keyed door lock
- Magnetic door gaskets for positive seal
- 3 adjustable shelves

Materials

- Stainless steel exterior
- White-powder coated aluminum interior with stainless steel floor

Dimensions

- 26 7/8" W x 34 3/4" L x 83 1/4" H
- 77 1/2" H without casters

Capacity

- 23 cu. ft.

Utilities / Power

115V, 60 HZ, 3 AMPS, 1/5 HP

Controls

- Digital display microprocessor temperature controller
- Adjustable operating temperature: 34°F to 50°F (1°C to 10°C)
- Audible and visual hi/lo temperature alarm

Performance

- 2 probes: 1 in air and 1 in sample bottle
- Sensor error alarm
- Continuous product temperature display
- Remote alarm contacts
- Forced draft air circulation
- LED interior lights are safety shielded and switch controlled

Other

- Easily cleaned smooth interior
- Cycle defrost
- Additional shelves may be purchased



www.mopec.com

800.362.8491

800 Tech Row

Madison Heights, MI 48071