



# Three Body Economy Cooler

## KF301

\* specifications of modified models may vary from the model shown.

## Specifications

### Construction

- NSF and UL approved
- Stucco galvanized steel finish on interior and exterior
- Unit ships assembled. Self contained top mount unit ships loose.

### Dimensions

- 2' 11" W x 7' 8" D
- 7' 6" H with condenser
- 6' 4" H without condenser

### Warranty

- 1 Year warranty



### Panels

- 4" panels with foamed-in-place polyurethane insulation
- Panels lock together with cam lock system

### Rack System

- Three tier storage rack with solid conveyor rollers
- (3) 23" HD-polyethylene transfer boards
- 300 lbs per tier weight capacity



### Doors

- (1) 28" W x 60" H door
- (1) Spring action door closer
- (1) 9" Diamond tread kick plate on interior and exterior of door

### Features

- (2) 4" Ridged non-swivel casters
- (2) 4" Swivel casters with brake
- (1) 2" Dial thermometer

### Refrigeration

- Heatcraft self-contained top mount system
- 35° operating temperature
- R-404a refrigerant
- 115v/60hz/1ph (plug supplied), Max fuse 15 amps
- No plumbing required
- No HVAC required
- Total heat of rejection (THR) = 3,800btuh