Lab Refrigerator, Upright - KG Series

General Purpose Solid Door Stainless Steel Refrigerator with digital display microprocessor temperature controller. This unit features hydrocarbon natural refrigerants and sensor error alarm and remote alarm contacts. Audible and visual high/low alarms and forced draft circulation are some of the features of this well rounded unit. Available in one door, two door, and three door options.



SPECIFICATIONS

Construction

- Modern, state-of-the-art styling
- Stainless steel front, aluminum end panels and interior
- Heavy duty, epoxy-coated steel shelves
- 3" non-CFC polyurethane foam insulation
- · Cam action lift off hinges
- 5" casters

Materials

Features

- Exterior: heavy gauge anodized aluminum with stainless steel door and hatch cover
- Interior: milled finish aluminum

Dimensions

- 1 door: 26" W x 35.375" D x 82.25" H
- 2 door: 52" W x 35.275" D x 82.25" H
- 3 door: 78" W x 35.375" D x 82.25" H

Performance

- Performance-rated refrigeration system utilizing environmentally safe R-134a refrigerant
- Self-closing doors with chrome-plated flow line handles
- Magnetic, snap-in door gasket
- Cylinder lock in each door
- Automatic interior lighting and electric condensate evaporator
- External dial thermometer

Model No.	Doors	Dimensions	Capacity	Shelves	Tray Capacity
KG100	1	26" W x 35.375" D x 82.25" H	20 cu. ft.	3	24 per section
KG200	2	52" W x 35.375" D x 82.25" H	48 cu. ft.	6	24 per section
KG300	3	78" W x 35.375" D x 82.25" H	70 cu. ft.	9	24 per section

Capacity

- 1 door: 20 cubic feet
- 2 door: 48 cubic feet
- 3 door: 70 cubic feet
- Number of shelves: 3 per section
- Tray slide capacity: 24 per section

Options & Accessories

- Freezer option available in all options
- 220v units available in all options



www. mopec.com 800.362.8491 800 Tech Row Madison Heights, MI 48071